FOR HANDRAILS, TOP RAILS, TREADS AND STAIRS

Operation and maintenance instructions

With declaration of contents. Handed over to the client when the delivery is complete.

Project _____

Delivery of _____

Contractor _____

Client's representative _____

Operation and care

Light dirt is removed with mild soap and lukewarm water. Scratches and heavier dirt are dealt with by sanding with fine sandpaper, after which the surface is treated with oil or clear lacquer. Stained surfaces are sanded lightly, touched up and then given clear lacquer. Oiled wooden surfaces outdoors should be oiled at least three times a year for the best durability. Always make sure oiled surfaces are saturated.

By finish

- **Clear lacquer.** Clean with an ordinary household cleaner and a well wrung-out cloth. Avoid scouring powder and cleaners containing abrasives or ammonia, and do not leave liquid standing. Remove stubborn marks carefully with white spirit. Tape, adhesive putty and hand cream can soften the lacquer.
- **Wood oil.** Oil when the surface feels dry. Apply until the wood is saturated and wipe off the excess after about 20 minutes. Do not oil in direct sunlight or below +5 °C.
- **Wax oil.** Clean with a lightly dampened cloth and a mild cleaner. Freshen up with maintenance wax. A worn surface is cleaned and given a new thin coat of the same wax oil.
- **Stainless fittings and end sleeves.** Clean with a stainless steel cleaner and a soft cloth, in the direction the steel is brushed. Never use steel wool or abrasive cleaners.

> **Oily rags can self-ignite.**
>
> Rags and cloths with oil or wax oil are put in water straight after use.

Maintenance of oiled handrails and top rails

Handrails and top rails are oiled three times at the factory with Chinese wood oil. Maintenance is to be carried out as needed and logged with the date and the name of the person who carried it out.

Date	Maintenance	Carried out by

Declaration of contents – finishes

- Deep-penetrating Chinese wood oil
- Clear lacquer: acid-curing two-component lacquer
- Stain: water-based

Guarantee

Guarantee period 2 years.

NB! During the guarantee period, Herrljunga Ledstångsfabrik accepts no liability for drying out and cracking of handrails and top rails for outdoor use caused by inadequate maintenance.

Environment and quality

We use timber of the best quality from established Swedish timber suppliers, all of whom have their own environmental policy, and we use no endangered species. Offcuts from production heat the factory all year round.

Herrljunga Ledstångsfabrik AB

Björkvägen, Box 102, 524 22 Herrljunga, Sweden · +46 (0)513-103 70 · info@hlf.se